



IP66 Protection

- Round terminal box, makes cleaning easier.
- Double lip seal at exit shaft to prevent water go inside.
- Round terminal with no gap for water/dust to get in.

FELIX Stainless Motor

High quality and robust stainless steel motor available from 0.37kw to 7.5kw both IEC/ANSI Standard.

Contact Us

Phone: 662-9104822

Email: sales@yutakaintertrade.com

Web: www.yutakaintertrade.com



**YUTAKA
INTERTRADE
CO.,LTD**

Industrial Product Supplier



**YUTAKA INTERTRADE
CO.,LTD**

217/4 RIMKLONGPRAPA
RD.,
BANGSU BANGKOK 10800



Available with TENV and TEFC

We can supply both of TENV (Totally Enclosed Non Ventilation) and TEFC (Total Enclosed Fan Cool) from 0.37kw to 7.5kw with B3, B5, B14, B35 AND B34 mounting available, (all parts interchangeable)

- Motors are to IEC dimensions
- 63 to 200 frame
- 0.18kw to 30kw
- 2 pole, 4 pole and 6 pole available



Winding end turns wrapped with epoxy for superior dielectric strength and rigidity

Double VPI winding treatment, greatly improves winding protection and low temperature rise

Anti-Fungal winding treatment to prevent humidity damage to windings

High quality 304 stainless welded steel frame to guarantee long lasting durability



Precision Balance Rotor

- Shaft extension has radius instead of undercut at the journal
- Premium motor grade sealed bearings same size at both ends
- Special NTN blue seal (orange seal) bearings, C3 clearance, rated -40.C up to +200.C. Double low friction rubber seals so no efficiency is lost
- Varnished rotor and laminations to prevent rust
- Double Lip Seal and Slinger
(The information in this document is subject to **change without notice**)